



WID-FR

Perforated Face Diffusers


Perforated Face Diffusers

WID-FR

Introduction

The ceiling diffuser WID-FR is a perforated ceiling grid. The diffuser is suitable for extraction above the suspended ceiling and is manufactured from a steel perforated plate.

To prevent view, the grille can be equipped with shall be fitted with a cover plate fitted with a insulation layer.



Features

- Standard color: RAL-9010
- Can be used for extracting air above ceiling
- Diffuser can be provided with see-through plate
- Can be used in standard modular ceiling systems
- Good aerodynamic properties
- Low noise level

Product description::

WID-FR	Square ceiling diffuser
WID FRA	Square ceiling diffuser with see-through plate





Technical details

Finishings

Front panel RAL 9010
 Cover plate black
 Other colours possible on request

Sizes

External size front plate 595x595mm



Selection table

WID-FR			
m ³ /h	l/s		
400	111	P _s	2
		L _p	-
500	139	P _s	4
		L _p	-
600	167	P _s	5
		L _p	-
750	208	P _s	9
		L _p	-
1000	278	P _s	15
		L _p	20
1250	347	P _s	24
		L _p	23

Selection example


WID-FR

qv (air volume) 1000 m³/h or 278 l/s
 Ps (pressure loss) 15 Pa
 Lp (sound pressure level) NR20

Order example

WID-FR / RAL9010

Diffuser type
 Finish





OC Waterloo
Ondernemersweg 2
7451 PK Holten

T 0548-374 375
E info@oc-waterloo.nl